Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: DC
Model identifier: LED12MG4LNW Type of light source: Lighting technology used: LED Non-directional or directional: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source: Mains or non-mains: NMLS Connected light source: Nein Envelope: - High luminance light source: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), 2,0 Standby power (Psb), expressed in W
Type of light source: Lighting technology used: Light source cap-type (or other electric interface) Mains or non-mains: Colour-tuneable light source: High luminance light source: Anti-glare shield: Product parameters Parameter Value Product parameters Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Light source: R4 Non-directional or directional or directional or directional: NDLS Non-directional: Non-directional or on NDLS Non-directional or directional or directional: NDLS Non-directional or NDLS Non-directional: Nein Source (CLS): Only with specific dimmers Parameter Value Parameter Value General product parameters: Energy efficiency class F Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set
Lighting technology used: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: Nein Anti-glare shield: Nein Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W LED Non-directional or directional or directional or directional: R4 Connected light Nein Nein Dimmable: Only with specific dimmers Parameter Value Parameter Value Fenergy efficiency class Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the same of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or
Light source cap-type (or other electric interface)
(or other electric interface) Mains or non-mains: NMLS Connected light source: Nein Envelope: - High luminance light source: Nein Anti-glare shield: Parameter Parameter Value Parameters Parameter Value Parameters Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Nein Envelope: - Nein Dimmable: Only with specific dimmers Value Parameter Value Parameter Value Parameter Value F Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set
Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: Nein Envelope: Anti-glare shield: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value Parameter: Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) (90°) On-mode power (Pon), expressed in W Nein Nein Nein Nein Envelope: - Conly with specific dimmers Value Parameter Value Parameter Value Parameter Value Parameter Value Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W
Source (CLS):
High luminance light source: Anti-glare shield: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value Parameter: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) (90°) On-mode power (Pon), expressed in W
Anti-glare shield: Nein Dimmable: Only with specific dimmers Parameter Parameter Value Parameter: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Parameter Value Parameter Value Parameter Value Parameter Value F Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the same of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W
Parameter Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) (90°) On-mode power (Pon), expressed in W Value Parameter Value F Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the same of correlated colour temperatures, rounded to the nearest 100 K, or the same of correlated colour temperatures, rounded to the nearest 100 K, or the same of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W
Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) (90°) On-mode power (Pon), expressed in W Energy efficiency class F Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W
General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer 2 Energy efficiency class F Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) 190 in Sphere (360°) temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W 2,0 Standby power (Psb), expressed in W 0,00
Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) (90°) Diagraphical Sphere (360°) Sphere (360°) Sphere (360°) The range of correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W Energy efficiency F Correlated colour temperature, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W
mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) Sphere (360°) (90°) On-mode power (Pon), expressed in W Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W
indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Sphere (360°) temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), expressed in W
expressed in W expressed in W
second decimal
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal The provided to the second decimal The provided to the nearest integer, or the range of CRI-values that can be set
OuterHeight30Spectral power distribution in theSee image in last page

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	9	range 250 nm to 800 nm, at full-load		
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-	
			Chromaticity	0,383	
			coordinates (x and y)	0,381	
Parameters for LED and OLED light sources:					
R9 colour rendering index value		50	Survival factor	0,90	
the lumen maintenance factor		0,70			

(a)نے : not applicable;

(b)_{'-'} : not applicable;

