Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: DC Supplier's address: Einkauf, Gewerbestraße 10, DE Model identifier: LED12MG4L/2 Type of light source: Lighting technology used: LED Non-directional or directional: Light source cap-type G4 (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: Nein Envelope: - High luminance light source: Nein Anti-glare shield: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value Parameter Value General product parameters:
Model identifier: LED12MG4L/2 Type of light source: Lighting technology used: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: Nein Anti-glare shield: Nein Product parameters Parameter Value General product parameters:
Type of light source: Lighting technology used: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: Nein Anti-glare shield: Nein Product parameters Parameter Value Parameter Value General product parameters:
Lighting technology used: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: Nein Envelope: - High luminance light source: Nein Anti-glare shield: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value General product parameters:
Light source cap-type G4 (or other electric interface) Mains or non-mains: NMLS Connected source (CLS): Colour-tuneable light source: Nein Envelope: - High luminance light source: Nein Dimmable: Only with specific dimmers Product parameters Value Parameter Value General product parameters:
(or other electric interface) Mains or non-mains: NMLS Connected light Nein source (CLS): Colour-tuneable light source: Nein Envelope: Nein Anti-glare shield: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value Parameter Value General product parameters:
Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: Nein Envelope: Nein Anti-glare shield: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value Parameter Value General product parameters:
source (CLS): Colour-tuneable light source: High luminance light source: Anti-glare shield: Nein Product parameters Parameter Value General product parameters:
High luminance light source: Anti-glare shield: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value Parameter Value General product parameters:
Anti-glare shield: Nein Dimmable: Only with specific dimmers Product parameters Parameter Value Parameter Value General product parameters:
Product parameters Parameter Value Parameter Value General product parameters:
Parameter Value Parameter Value General product parameters:
General product parameters:
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer 2 Energy efficiency G class
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) Sphere (360°) Sphere (360°) Sphere (360°) Sphere (360°) temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set
On-mode power (P_{on}) , $(P$
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal or the range of CRI-values that can be set
OuterHeight30Spectral power distribution in theSee image in last pagedimensionsWidth30distribution in thein last page

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	9	range 250 nm to 800 nm, at full-load		
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-	
			Chromaticity	0,423	
			coordinates (x and y)	0,420	
Parameters for LED and OLED light sources:					
R9 colour rendering index value		55	Survival factor	0,90	
the lumen maintenance factor		0,70			

(a)'-': not applicable;

(b)_{'-'} : not applicable;

