Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: DC

Supplier's address: Einkauf, Gewerbestraße 10, DE

Model identifier: LED18STG4LKW/2

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	G4		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	Nein
Colour-tuneable light source:	Nein	Envelope:	-
High luminance light source:	Nein		
Anti-glare shield:	Nein	Dimmable:	Only with specific dimmers

Product parameters

ParameterValueGeneral product produ	Parameter arameters: Energy efficiency class Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that	Value E 6 000
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer2Useful luminous flux (\$\phiuse\$), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)230 in Sphere (360°)On-mode expressed in W1,9Networked standby power (P_net)-	Energy efficiency class Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the	
mode (kWh/1000 h), rounded up to the nearest integer230 inUseful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)230 in Sphere (360°)On-mode power (Pon), expressed in W1,9Networked standby power (Pnet)-	class Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the	
indicating if it refers to the flux Sphere (360°) in a sphere (360°), in a wide Sphere (360°) cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W 1,9 Networked standby power (Pnet) -	temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the	6 000
expressed in W Networked standby power (P _{net}) -	can be set	
	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
for CLS, expressed in W and rounded to the second decimal	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80
Outer Height 34	500	See image
dimensions Width 19	Spectral power	

withoutDepthseparatecontrolgear,lightingcontrolpartsandnon-lightingcontrolparts,ifany(millimetre)	19	range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordinates (x and y)	0,321 0,348		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	-7	Survival factor	0,90		
the lumen maintenance factor	0,70				

(a)'-' : not applicable;

(b)'-' : not applicable;

