## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources  |              |                         |  |                            |  |  |  |
|--|--------------|-------------------------|--|----------------------------|--|--|--|
| Supplier's name or trade mark: DC  |              |                         |  |                            |  |  |  |
| Supplier's address: Einkauf, Gewerbestraße 10, DE  |              |                         |  |                            |  |  |  |
| Model identifier: LED15SU4L  |              |                         |  |                            |  |  |  |
| Type of light so   | urce:        |                         |  |                            |  |  |  |
| Lighting technology used:  |              | LED                     | Non-directional or directional:  | NDLS                       |  |  |  |
| Light source cap-type  |              | GU4                     |  |                            |  |  |  |
| (or other electri  | c interface) |                         |  |                            |  |  |  |
| Mains or non-mains:  |              | NMLS                    | Connected light source (CLS):  | Nein                       |  |  |  |
| Colour-tuneable light source:  |              | Nein                    | Envelope:  | -                          |  |  |  |
| High luminance light source:   |              | Nein                    |  |                            |  |  |  |
| Anti-glare shield:   |              | Nein                    | Dimmable:  | Only with specific dimmers |  |  |  |
| Product parameters   |              |                         |  |                            |  |  |  |
| Parameter  |              | Value                   | Parameter  | Value                      |  |  |  |
| General product parameters:  |              |                         |  |                            |  |  |  |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer   |              | 2                       | Energy efficiency class  | G                          |  |  |  |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |              | 115 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700                      |  |  |  |
| On-mode power (P <sub>on</sub> ), expressed in W   |              | 1,5                     | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal  | 0,00                       |  |  |  |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal                                |              | -                       | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 95                         |  |  |  |
| Outer  | Height       | 35                      | Spectral power distribution in the   | See image                  |  |  |  |
| dimensions   | Width        | 35                      |  | in last page               |  |  |  |

| without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | Depth | 35   | range 250 nm to 800<br>nm, at full-load |       |  |  |  |
|--|-------|------|---|-------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>   |       | -    | If yes, equivalent power (W)            | -     |  |  |  |
|  |       |      | Chromaticity                            | 0,459 |  |  |  |
|  |       |      | coordinates (x and y)                   | 0,412 |  |  |  |
| Parameters for LED and OLED light sources:   |       |      |   |       |  |  |  |
| R9 colour rendering index value  |       | 80   | Survival factor                         | 0,90  |  |  |  |
| the lumen maintenance factor   |       | 0,70 |   |       |  |  |  |

(a)'-': not applicable;

(b)<sub>'-'</sub> : not applicable;

