Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources							
Supplier's name or trade mark: DC							
Supplier's address: Einkauf, Gewerbestraße 10, DE							
Model identifier: LED30STBADLKW							
Type of light so	urce:						
Lighting technol	logy used:	LED	Non-directional or directional:	NDLS			
Light source cap-type		BA15d					
(or other electri	c interface)						
Mains or non-m	ains:	NMLS	Connected light source (CLS):	Nein			
Colour-tuneable	e light source:	Nein	Envelope:	-			
High luminance light source:		Nein					
Anti-glare shield:		Nein	Dimmable:	Only with specific dimmers			
Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		3	Energy efficiency class	E			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		370 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500			
On-mode power (P _{on}), expressed in W		3,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80			
Outer	Height	47	Spectral power	See image			
dimensions	Width	22	distribution in the	in last page			

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	22	range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-			
			Chromaticity	0,310			
			coordinates (x and y)	0,336			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		4	Survival factor	0,90			
the lumen maintenance factor		0,70					

(a)'-': not applicable;

(b)_{'-'} : not applicable;

