Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: DC

Supplier's address: Einkauf, Gewerbestraße 10, DE

Model identifier: LED29RLT5KW

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	G5					
(or other electric interface)						
Mains or non-mains:	NMLS	Connected light source (CLS):	Nein			
Colour-tuneable light source:	Nein	Envelope:	-			
High luminance light source:	Nein					
Anti-glare shield:	Nein	Dimmable:	No			
Product parameters						

Parameter Value Parameter Value General product >====================================			i iouuci para		T			
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer6Energy efficiency classEUseful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)720 in Sphere (360°)Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set5 000On-mode power (Pon), expressed in W6,0Standby power (Psb), expressed in W and rounded to the second decimal0,00Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal-Colour rendering index, rounded to the nearest integer, or the range of CRI-80	Parameter		Value	Parameter	Value			
mode (kWh/1000 h), rounded up to the nearest integerclassUseful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)720 in Sphere (360°)Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set5 000On-mode power (Pon), expressed in W6,0Standby power (Psb), expressed in W0,00Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal-Colour rendering index, rounded to the nearest integer, or the range of CRI-80	General product parameters:							
indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)Sphere (360°)temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be setOn-mode power (Pon), expressed in W6,0Standby power (Psb), expressed in W and rounded to the second decimal0,00Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal-Colour rendering index, rounded to the nearest integer, or the range of CRI-	mode (kWh/10	00 h), rounded	6		E			
expressed in W expressed in W and rounded to the second decimal Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal 0 the nearest integer, 0 or the range of CRI-	indicating if it r in a sphere (3 cone (120 ^o) or i	efers to the flux 60°), in a wide		temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that	5 000			
for CLS, expressed in W and rounded to the second decimalindex, rounded to the nearest integer, or the range of CRI-		oower (P _{on}),	6,0	expressed in W and rounded to the	0,00			
set	for CLS, expres	ssed in W and	-	index, rounded to the nearest integer, or the range of CRI- values that can be	80			
Outer Height 288 Spectral power See image	Outer dimensions without	Height	288	Spectral power	See image			
		Width	16	distribution in the	in last page			
Depth 16		Depth	16	1	Seite 1 / 3			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity	0,346			
		coordinates (x and y)	0,360			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	2	Survival factor	0,90			
the lumen maintenance factor	0,70					
(a)						

(a)_{'-'} : not applicable;

(b)'-' : not applicable;

