Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: DC Supplier's address: Einkauf, Gewerbestraße 10, DE Model identifier: LED6MBASL Type of light source: Lighting technology used: LED Non-directional or directional: Light source cap-type BA15s (or other electric interface) Mains or non-mains: NMLS Connected light Nein source (CLS): Colour-tuneable light source: Nein Envelope: - High luminance light source: Nein Dimmable: Only with specific dimmers Product parameter Parameter Value Parameter Value General product parameters: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (3609), in a narrow cone (900) Useful condition in a narrow cone (900) On-mode power (Pon), 1,0 Standby power (Psn), or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest look that can be set On-mode power (Pon), 1,0 Standby power (Psn), expressed in W and rounded to the second decimal Networked standby power (Pnet) of CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) of CLS, expressed in W and rounded to the second decimal Outer Height 37 Special power distribution in the inlast page distribution in the inlast page	sources								
Type of light source: Lighting technology used: Light source cap-type (or other electric interface) Mains or non-mains: Colour-tuneable light source: Nein Non-directional: Non-directional: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: Nein Nein Dimmable: Only with specific dimmers Product parameters Parameter Value Parameter Value Parameter Value Parameter: Value General product parameters: Energy consumption in onde (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360%), in a wide cone (120%) or in a narrow cone (90%) On-mode power (Pon), 200 Standby power (Pso), expressed in W and rounded to the nearest 100 K, and be set On-mode power (Pon), 1,0 Standby power (Pso), expressed in W and rounded to the second decimal Networked standby power (Pnet) of CLS, expressed in W and rounded to the nearest integer, or the range of CRI-values that can be set Outer Height 37 Spectral power See image	Supplier's name or trade mark: DC								
Lighting technology used: Lighting technology used: Light source cap-type (or other electric interface) Mains or non-mains: Colour-tuneable light source: High luminance light source: Nein Anti-glare shield: Nein Product parameter Value Parameter Value Parameter: Corelated colour temperature, rounded up to the nearest integer Useful luminous flux (фuse), in a wide cone (120°) or in a narrow cone (90°) On-mode power (P _{om}), expressed in W Networked standby power (P _{om}) Networked standby power (P _{om}) Networked standby power (P _{om}) Outer Height Height Anti-glare shield: Nein Nein Envelope: - Nein Dimmable: Only with source: Parameter Value Parameter Value Parameter: Value Parameter: Value Value Parameter: Value Parameter: Value Parameter: Value Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, or the range of colour temperatures, rounded to the nearest 100 K, or the range of colour temperatures, rounded to the nearest 100 K, or the range of colour temperatures, rounded to the nearest 100 K, or the range of colour temperature, rounded to the nearest 100 K, or the range of colour temperature, rounded to the nearest 100 K, or the range of colour temperature, rounded to the nearest 100 K, or the range of colour temperature, rounded to the nearest integer, or the range of colour temperatu	Supplier's address: Einkauf, Gewerbestraße 10, DE								
Lighting technology used: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source: Nein Envelope: - High luminance light source: Nein Product parameters Parameter Value Reneral product parameters: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Outer Height Non-directional or directional: NALS Connected light Nein Senvelope: Colour rendering in the filation in the nearest integer, or the range of CRI-values that can be set Sel image Nein Senvelope: Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set Outer Height 37 Spectral power See image	Model identifier: LED6MBASL								
Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source color source (CLS): Colour-tuneable light source: Nein Anti-glare shield: Nein Product parameters Parameter Value Parameter Value Parameters Parameter Value Reneral product parameters: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the nearest integer, or the range of CRI-values that can be set Outer Height 37 Spectral power See image	Type of light source:								
Cor other electric interface) Mains or non-mains: NMLS Connected light Source (CLS):	Lighting technology used:		LED		NDLS				
Mains or non-mains: Colour-tuneable light source: Nein Anti-glare shield: Nein Product parameters Parameter Value Parameter Value Parameter: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), in a sphere (360°), in a narrow cone (90°) On-mode power (Pon), expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Outer Height Nein Envelope: Nein Dimmable: Only with specific dimmers Only with specific dimmers Value Parameter Value Parameter Value Parameter Value Parameter Value Parameter Value Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode power (Pon), 1,0 Standby power (Psb), expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the nearest integer, or the range of CRI-values that can be set Outer Height 37 Spectral power See image	Light source cap-type		BA15s						
Source (CLS): Colour-tuneable light source: High luminance light source: Anti-glare shield: Nein Product parameters Parameter Value General product parameters: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Outer Height 37 Spectral power See image	(or other electric interface)								
High luminance light source: Anti-glare shield: Nein Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Outer Height 37 Spectral power See image	Mains or non-mains:		NMLS		Nein				
Product parameters Parameter Value Parameter Value Parameter Value General product parameters Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked to the second decimal	Colour-tuneable light source:		Nein	Envelope:	-				
Parameter Value Parameter Value Seneral product parameters Energy consumption in onmode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Outer Height 37 Spectral power See image	High luminance light source:		Nein						
Parameter Value Parameter Value Parameter Value	Anti-glare shield:		Nein	Dimmable:	•				
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Outer Height 37 Spectral power See image	Product parameters								
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Outer Height 37 Spectral power See image	Parameter		Value	Parameter	Value				
mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Networked to the second decimal Networked to the second decimal Outer Height 37 Spectral power See image	General product parameters:								
indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) On-mode power (Pon), expressed in W and rounded to the second decimal Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal Outer Height 37 Spectral power See image	mode (kWh/1000 h), rounded		1	,	F				
expressed in W and rounded to the second decimal Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal The second decimal rounded to the second decimal the nearest integer, or the range of CRI-values that can be set Outer Height 37 Spectral power See image	indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone		Sphere (360°)	temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set					
for CLS, expressed in W and rounded to the second decimal index, rounded to the nearest integer, or the range of CRI-values that can be set Outer Height 37 Spectral power See image	1 (0117)		1,0	expressed in W and rounded to the	0,00				
	for CLS, expressed in W and rounded to the second decimal		-	index, rounded to the nearest integer, or the range of CRI- values that can be set					
	Outer dimensions	Height Width	27	Spectral power distribution in the	See image in last page				

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	27	range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-			
			Chromaticity	0,446			
			coordinates (x and y)	0,406			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		5	Survival factor	0,90			
the lumen main	the lumen maintenance factor						

(a)'-': not applicable;

(b)_{'-'} : not applicable;

